

TYRES

Product group	Tyres
Item number	10927560
Valid tyre size	280 / 85 R 20
LI / SI / PR	112 A8 / 112 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.

Technical Informations

Item number	10927560
EAN	8059971054903
Valid tyre size	280 / 85 R 20
Alternative size 1	11.2R20
LI / SI / PR	112 A8 / 112 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	42,00
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	299
Outer diameter of tyre [mm].	981
Stat. radius (SLR) [mm]	444
Speed Radius Index (SRI)	475
Rolling circumference [mm].	2934
Tread depth (mm)	37,0
Number of lugs	17x2
Lug width (mm)	38
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 A8	1120	40		1,60	
112 B	1120	50		1,60	