

TYRES

Product group	Tyres
Item number	10927570
Valid tyre size	280 / 70 R 20
LI / SI / PR	116 A8 / 116 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T



Mitas

Notes and features

- The AC 70 T is a tractor tyre for heavy field work.
- Its high lugs provide excellent traction.

- Reduced slip thanks to its outstanding self-cleaning properties.
- The tyre is characterised by its versatility and can also be used in vineyards and orchards, for example.



Technical Informations

Item number	10927570
EAN	8059971040128
Valid tyre size	280 / 70 R 20
LI / SI / PR	116 A8 / 116 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	31,40
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	2,40
Section width (mm)	276
Outer diameter of tyre [mm].	906
Stat. radius (SLR) [mm]	411
Speed Radius Index (SRI)	425
Rolling circumference [mm].	2725
Tread depth (mm)	33,0
Number of lugs	17x2
Lug width (mm)	37
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A8	1250	40		2,40	
116 B	1250	50		2,40	