# Bohnenkamp Moving Professionals

20.09.2024

### **TYRES**

Product group	Tyres
Item number	10927575
Valid tyre size	320 / 70 R 20
LI / SI / PR	113 A8 / 113 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T



Mitas

#### Notes and features

- The AC 70 T is a tractor tyre for heavy field work.
- Its high lugs provide excellent traction.

- Reduced slip thanks to its outstanding self-cleaning properties.
- The tyre is characterised by its versatility and can also be used in vineyards and orchards, for example.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10927575
EAN	8059971064452
Valid tyre size	320 / 70 R 20
LI / SI / PR	113 A8 / 113 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	43,40
Recommended rim size	10
Permitted rim size	11, 9
Maximum air pressure [bar].	1,60
Section width (mm)	320
Outer diameter of tyre [mm].	972
Stat. radius (SLR) [mm]	441
Speed Radius Index (SRI)	475
Rolling circumference [mm].	2916
Tread depth (mm)	36,0
Lug width (mm)	40
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
113 A8	1150	40		1,60	
113 B	1150	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.