

TYRES

Product group	Tyres
Item number	10927620
Valid tyre size	445 / 65 R 22.5
LI / SI / PR	160 G
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 +



Mitas

Notes and features

• Multi-purpose tyre for grassland, fields and roads.

• Up to 90 km/h.



Technical Informations

Item number	10927620
EAN	8059971043433
Valid tyre size	445 / 65 R 22.5
LI / SI / PR	160 G
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 +
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	105,64
Recommended rim size	14
Permitted rim size	13
Maximum air pressure [bar].	6,00
Section width (mm)	450
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	536
Rolling circumference [mm].	3525
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 G	4500	90		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.