

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 10927630 |
| Valid tyre size | 320 / 85 R 24 |
| LI / SI / PR | 122 A8 / 122 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 85 |



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



Technical Informations

| Item number | 10927630 |
|------------------------------|----------------|
| EAN | 8059971064063 |
| Valid tyre size | 320 / 85 R 24 |
| LI / SI / PR | 122 A8 / 122 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 85 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 55,30 |
| Recommended rim size | 11 |
| Permitted rim size | 9, 10 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 343 |
| Outer diameter of tyre [mm]. | 1158 |
| Stat. radius (SLR) [mm] | 530 |
| Speed Radius Index (SRI) | 550 |
| Rolling circumference [mm]. | 3484 |
| Tread depth (mm) | 40,0 |
| Number of lugs | 19x2 |
| Lug width (mm) | 36 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 122 A8 | 1500 | 40 | | 1,60 | |
| 122 B | 1500 | 50 | | 1,60 | |