# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres
Item number	10927665
Valid tyre size	380 / 70 R 24
LI / SI / PR	128 A8 / 125 D
TL/TT	TL
Brand	Mitas
Tread pattern	HC 70



Mitas

#### Notes and features

- The HC 70 is an all-round wide-base tyre with increased . loading capacity.
- Its tread pattern provides excellent traction. •
- Due to rounded lug edges and a round shoulder design, . the soil is effectively protected, particularly during work on grassland.
- The wide tyre shoulder guarantees excellent ride comfort . on the road.
- Economical operational costs thanks to minimised slip. •

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10927665
EAN	8059971056778
Valid tyre size	380 / 70 R 24
LI / SI / PR	128 A8 / 125 D
TL/TT	TL
Brand	Mitas
Tread pattern	HC 70
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	69,20
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	1,60
Section width (mm)	395
Outer diameter of tyre [mm].	1191
Stat. radius (SLR) [mm]	533
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3545
Tread depth (mm)	40,0
Number of lugs	18x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40		1,60	
125 D	1650	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.