

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 10927740 |
| Valid tyre size | 500 / 85 R 24 |
| LI / SI / PR | 158 A8 / 171 A8 |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | SFT |



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 10927740 |
| EAN | 8059971036985 |
| Valid tyre size | 500 / 85 R 24 |
| LI / SI / PR | 158 A8 / 171 A8 |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | SFT |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 133,30 |
| Recommended rim size | 16 |
| Permitted rim size | 15 |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 528 |
| Outer diameter of tyre [mm]. | 1458 |
| Stat. radius (SLR) [mm] | 621 |
| Rolling circumference [mm]. | 4237 |
| Tread depth (mm) | 38,0 |
| Number of lugs | 20x2 |
| Lug width (mm) | 43 |
| Tyre capacity 75% [ltr.] | 310 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 A8 | 4250 | 40 | Drive Wheel | 2,80 | |
| 171 A8 | 6150 | 40 | Free Rolling | 2,80 | |