Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 10927750 |
| Valid tyre size | 540 / 65 R 24 |
| LI / SI / PR | 143 A8 / 140 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 65 |



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the . field and on the road.
- Thanks to its wide contact area, the soil is protected • effectively.
- The wear-resistant rubber compound ensures a long . service life.
- The tyre is characterised by a large air volume, • guaranteeing a high transport performance.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 10927750 |
|------------------------------|----------------|
| EAN | 8059971056907 |
| Valid tyre size | 540 / 65 R 24 |
| LI / SI / PR | 143 A8 / 140 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 65 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 99,40 |
| Recommended rim size | 16 |
| Permitted rim size | 18, 15 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 523 |
| Outer diameter of tyre [mm]. | 1317 |
| Stat. radius (SLR) [mm] | 590 |
| Speed Radius Index (SRI) | 625 |
| Rolling circumference [mm]. | 3922 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 19x2 |
| Lug width (mm) | 41 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 143 A8 | 2725 | 40 | | 1,60 | |
| 140 D | 2500 | 65 | | 1,60 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.