

## **TYRES**

Product group	Tyres	
Item number	10927760	
Valid tyre size	280 / 85 R 28	
LI / SI / PR	118 A8 / 118 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 85	



Mitas

## Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



## **Technical Informations**

Item number	10927760
EAN	8059971064001
Valid tyre size	280 / 85 R 28
LI / SI / PR	118 A8 / 118 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	49,40
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	298
Outer diameter of tyre [mm].	1190
Stat. radius (SLR) [mm]	551
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3582
Tread depth (mm)	37,0
Number of lugs	21x2
Lug width (mm)	37
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A8	1320	40		1,60	
118 B	1320	50		1,60	