

TYRES

Product group	Tyres
Item number	10927820
Valid tyre size	480 / 70 R 28
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T



Mitas

Notes and features

- The AC 70 T is a tractor tyre for heavy field work.
- Its high lugs provide excellent traction.

- Reduced slip thanks to its outstanding self-cleaning properties.
- The tyre is characterised by its versatility and can also be used in vineyards and orchards, for example.



Technical Informations

Item number	10927820
EAN	8059971057683
Valid tyre size	480 / 70 R 28
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	99,70
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	480
Outer diameter of tyre [mm].	1415
Stat. radius (SLR) [mm]	630
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4206
Tread depth (mm)	52,0
Number of lugs	18x2
Lug width (mm)	45
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		1,60	
140 B	2500	50		1,60	