

## TYRES

Product group	Tyres
Item number	10927835
Valid tyre size	540 / 65 R 28
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp  
■ ■ ● Moving Professionals

**Mitas**

## Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

## Technical Informations

Item number	10927835
EAN	8059971037869
Valid tyre size	540 / 65 R 28
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	119,00
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	540
Outer diameter of tyre [mm].	1414
Stat. radius (SLR) [mm]	627
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4210
Tread depth (mm)	48,0
Lug width (mm)	46-55
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
142 D	2650	65		1,60	