

TYRES

Product group	Tyres	
Item number	10927850	
Valid tyre size	600 / 65 R 28	
LI / SI / PR	157 A8 / 154 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	SFT	



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



Technical Informations

Item number	10927850
EAN	8059971037401
Valid tyre size	600 / 65 R 28
LI / SI / PR	157 A8 / 154 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	160,10
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	606
Outer diameter of tyre [mm].	1494
Stat. radius (SLR) [mm]	664
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4444
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		2,40	
154 D	3750	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.