

TYRES

Product group	Tyres
Item number	10927900
Valid tyre size	540 / 65 R 30
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10927900
EAN	8059971035148
Valid tyre size	540 / 65 R 30
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	121,50
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	2,40
Section width (mm)	526
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	664
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4419
Tread depth (mm)	48,0
Number of lugs	21x2
Lug width (mm)	43
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		2,40	
150 D	3350	65		2,40	