

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 10927920       |
| Valid tyre size | 600 / 70 R 30  |
| LI / SI / PR    | 155 A8 / 152 D |
| TL/TT           | TL             |
| Brand           | Mitas          |
| Tread pattern   | SFT            |



Mitas

## Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



## **Technical Informations**

| Item number                  | 10927920       |
|------------------------------|----------------|
| EAN                          | 8059971039764  |
| Valid tyre size              | 600 / 70 R 30  |
| LI / SI / PR                 | 155 A8 / 152 D |
| TL/TT                        | TL             |
| Brand                        | Mitas          |
| Tread pattern                | SFT            |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 177,40         |
| Recommended rim size         | 18             |
| Permitted rim size           | 20             |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 625            |
| Outer diameter of tyre [mm]. | 1595           |
| Stat. radius (SLR) [mm]      | 700            |
| Rolling circumference [mm].  | 4700           |
| Tread depth (mm)             | 54,0           |
| Number of lugs               | 19x2           |
| Lug width (mm)               | 54             |
| E-Ready                      | No             |



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 155 A8 | 3875               | 40           |               | 1,60                        |              |
| 152 D  | 3550               | 65           |               | 1,60                        |              |