

## TYRES

Product group	Tyres
Item number	10927920
Valid tyre size	600 / 70 R 30
LI / SI / PR	155 A8 / 152 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp  
■ ■ ● Moving Professionals

**Mitas**

## Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

## Technical Informations

Item number	10927920
EAN	8059971039764
Valid tyre size	600 / 70 R 30
LI / SI / PR	155 A8 / 152 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	177,40
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	625
Outer diameter of tyre [mm].	1595
Stat. radius (SLR) [mm]	700
Rolling circumference [mm].	4700
Tread depth (mm)	54,0
Number of lugs	19x2
Lug width (mm)	54
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		1,60	
152 D	3550	65		1,60	