Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres
Item number	10927922
Valid tyre size	620 / 70 R 30
LI / SI / PR	178 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10927922
EAN	8059971043792
Valid tyre size	620 / 70 R 30
LI / SI / PR	178 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	204,50
Recommended rim size	18
Permitted rim size	20, 21
Maximum air pressure [bar].	2,40
Section width (mm)	625
Outer diameter of tyre [mm].	1595
Stat. radius (SLR) [mm]	680
Rolling circumference [mm].	4770
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40	Free Rolling	2,40	
166 A8	5300	40	Drive Wheel	2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.