

TYRES

Product group	Tyres
Item number	10927923
Valid tyre size	620 / 75 R 30
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927923
EAN	8059971059809
Valid tyre size	620 / 75 R 30
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	207,80
Recommended rim size	DW20B
Permitted rim size	DW18L, DW21B
Maximum air pressure [bar].	2,80
Section width (mm)	635
Outer diameter of tyre [mm].	1700
Stat. radius (SLR) [mm]	740
Speed Radius Index (SRI)	800
Rolling circumference [mm].	4980
Tread depth (mm)	54,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	550
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		2,80	
166 D	5300	65		2,80	