Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10927925
Valid tyre size	710 / 55 R 30
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance • machines above180 hp.
- Its big contact area provides excellent traction. •
- The flexible sidewalls enable high load capacities even at . low inflation pressure.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10927925
EAN	8059971065886
Valid tyre size	710 / 55 R 30
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	192,90
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	690
Outer diameter of tyre [mm].	1500
Stat. radius (SLR) [mm]	674
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4475
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
159 D	4375	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.