

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10928048 |
| Valid tyre size | 600 / 65 R 34 |
| LI / SI / PR | 160 A8 / 157 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 65 |



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10928048 |
| EAN | 8059971054798 |
| Valid tyre size | 600 / 65 R 34 |
| LI / SI / PR | 160 A8 / 157 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 65 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 153,00 |
| Recommended rim size | W18L |
| Permitted rim size | W16L, DW20B |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 592 |
| Outer diameter of tyre [mm]. | 1664 |
| Stat. radius (SLR) [mm] | 740 |
| Rolling circumference [mm]. | 4915 |
| Tread depth (mm) | 51,0 |
| Number of lugs | 21x2 |
| Tyre capacity 75% [ltr.] | 465 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 A8 | 4500 | 40 | | 2,40 | |
| 157 D | 4125 | 60 | | 2,40 | |