

TYRES

Product group	Tyres	
Item number	10928110	
Valid tyre size	340 / 85 R 38	
LI / SI / PR	133 A8 / 133 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 85	



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



Technical Informations

Item number	10928110
EAN	8059971064612
Valid tyre size	340 / 85 R 38
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	82,80
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	365
Outer diameter of tyre [mm].	1562
Stat. radius (SLR) [mm]	719
Rolling circumference [mm].	4685
Tread depth (mm)	40,0
Number of lugs	24x2
Lug width (mm)	37
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,60	
133 B	2060	50		1,60	