

TYRES

Product group	Tyres	
Item number	10928180	
Valid tyre size	460 / 85 R 38	
LI / SI / PR	149 A8 / 149 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 85	



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



Technical Informations

Item number	10928180
EAN	8059971040265
Valid tyre size	460 / 85 R 38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	140,10
Recommended rim size	16
Permitted rim size	14, 15
Maximum air pressure [bar].	1,60
Section width (mm)	508
Outer diameter of tyre [mm].	1768
Stat. radius (SLR) [mm]	805
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5280
Tread depth (mm)	51,0
Number of lugs	22x2
Lug width (mm)	45
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
149 B	3250	50		1,60	