

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10928195 |
| Valid tyre size | 650 / 65 R 38 |
| LI / SI / PR | 160 A8 / 157 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | SFT |



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10928195 |
| EAN | 8059971040586 |
| Valid tyre size | 650 / 65 R 38 |
| LI / SI / PR | 160 A8 / 157 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | SFT |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 214,40 |
| Recommended rim size | W18L |
| Permitted rim size | DW20B, DW21B |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 645 |
| Outer diameter of tyre [mm]. | 1828 |
| Stat. radius (SLR) [mm] | 810 |
| Speed Radius Index (SRI) | 875 |
| Rolling circumference [mm]. | 5445 |
| Tread depth (mm) | 57,0 |
| Number of lugs | 20x2 |
| Lug width (mm) | 59 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 A8 | 4500 | 40 | | 1,60 | |
| 157 D | 4125 | 65 | | 1,60 | |