

TYRES

Product group	Tyres
Item number	10928205
Valid tyre size	800 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928205
EAN	8059971054736
Valid tyre size	800 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	374,30
Recommended rim size	25
Permitted rim size	27
Maximum air pressure [bar].	2,40
Section width (mm)	765
Outer diameter of tyre [mm].	2052
Stat. radius (SLR) [mm]	911
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6090
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		2,40	
178 D	7500	65		2,40	