

TYRES

Product group	Tyres
Item number	10928240
Valid tyre size	650 / 75 R 42
LI / SI / PR	168 A8 / 165 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928240
EAN	8059971059793
Valid tyre size	650 / 75 R 42
LI / SI / PR	168 A8 / 165 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	267,00
Recommended rim size	21
Permitted rim size	20, 23
Maximum air pressure [bar].	1,60
Section width (mm)	650
Outer diameter of tyre [mm].	2035
Stat. radius (SLR) [mm]	905
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6090
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		1,60	
165 D	5150	65		1,60	