

## **TYRES**

Product group	Tyres
Item number	10928250
Valid tyre size	710 / 70 R 42
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

## Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



## **Technical Informations**

Item number	10928250
EAN	8059971062311
Valid tyre size	710 / 70 R 42
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	359,00
Recommended rim size	23
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	731
Outer diameter of tyre [mm].	2070
Stat. radius (SLR) [mm]	935
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6150
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 D	6500	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.