

TYRES

Product group	Tyres
Item number	10928250
Valid tyre size	710 / 70 R 42
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928250
EAN	8059971062311
Valid tyre size	710 / 70 R 42
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	359,00
Recommended rim size	23
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	731
Outer diameter of tyre [mm].	2070
Stat. radius (SLR) [mm]	935
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6150
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 D	6500	65		2,40	