

TYRES

Product group	Tyres
Item number	10928255
Valid tyre size	710 / 75 R 42
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928255
EAN	8059971039740
Valid tyre size	710 / 75 R 42
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	362,50
Recommended rim size	23
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	751
Outer diameter of tyre [mm].	2171
Stat. radius (SLR) [mm]	971
Speed Radius Index (SRI)	1000
Rolling circumference [mm].	6460
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		2,40	
175 D	6900	65		2,40	