Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres	
Item number	10935030	
Valid tyre size	10.5 R 20	
LI / SI / PR	134 J, 14 PR	
TL/TT	TL	
Brand	Continental	
Tread pattern	MPT 80	





Notes and features

- The MPT 80 is ideally suited for use on multi-purpose vehicles on paved and unpaved roads.
- Large lug tread contact area.

- High-traction tread pattern.
- Increased traction and high mileage.
- Ensured mobility on soft soils.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10935030
EAN	4040658007705
Valid tyre size	10.5 R 20
LI / SI / PR	134 J, 14 PR
TL/TT	ТL
Brand	Continental
Tread pattern	MPT 80
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	38,90
Recommended rim size	9
Permitted rim size	8
Maximum air pressure [bar].	5,25
Section width (mm)	265
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	444
Rolling circumference [mm].	2865
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 J	2120	100		5,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.