

TYRES

Product group	Tyres	
Item number	10935071	
Valid tyre size	12.5 R 20	
LI / SI / PR	147 J, 22 PR	
TL/TT	TL	
Brand	Continental	
Tread pattern	MPT 80	





Notes and features

- The MPT 80 is ideally suited for use on multi-purpose vehicles on paved and unpaved roads.
- Large lug tread contact area.

- High-traction tread pattern.
- Increased traction and high mileage.
- Ensured mobility on soft soils.



Technical Informations

Item number	10935071
EAN	4040658007736
Valid tyre size	12.5 R 20
LI / SI / PR	147 J, 22 PR
TL/TT	TL
Brand	Continental
Tread pattern	MPT 80
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	52,40
Recommended rim size	11
Permitted rim size	11-20SDC
Maximum air pressure [bar].	6,50
Section width (mm)	320
Outer diameter of tyre [mm].	1030
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3120
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 J	3075	100		6,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.