Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	10936360
Valid tyre size	445 / 70 R 24
LI / SI / PR	151 G
TL/TT	TL
Brand	Mitas
Tread pattern	MPT-22



Mitas

Notes and features

- The EM-02 has a typical tractor tread pattern with very good traction properties.
- It is characterised above all by excellent durability.
- The tyre is particularly suitable for use on compact construction machines such as small loaders, telescopic loaders or similar vehicles.
- But it can be used on agricultural machinery as well.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10936360
EAN	8590341003201
Valid tyre size	445 / 70 R 24
Alternative size 1	17.5R24
LI / SI / PR	151 G
TL/TT	т
Brand	Mitas
Tread pattern	MPT-22
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	89,60
Recommended rim size	15
Maximum air pressure [bar].	4,10
Section width (mm)	465
Outer diameter of tyre [mm].	1255
Stat. radius (SLR) [mm]	573
Rolling circumference [mm].	3765
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 G	3450	90		4,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.