

TYRES

Product group	Tyres
Item number	10966055
Valid tyre size	7.50 R 15
LI / SI / PR	135 / 133 G (134 / 132 J)
TL/TT	TT
Brand	Semperit
Tread pattern	M422 Trailer-Steel



Bohnenkamp
■ ■ ● Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit M422 is truck tyre for trailer axles for regional and long-haul transport.
- Thanks to its wide tread pattern and optimum pressure distribution, the tyre offers even wear and a long service life.
- The special shoulder grooves enable very good directional stability.

Technical Informations

Item number	10966055
EAN	4024067003572
Valid tyre size	7.50 R 15
LI / SI / PR	135 / 133 G (134 / 132 J)
TL/TT	TT
Brand	Semperit
Tread pattern	M422 Trailer-Steel
Axle position truck	TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	23,47
Recommended rim size	6.00
Permitted rim size	5.00, 5.50, 6.50
Maximum air pressure [bar].	8,50
Section width (mm)	191
Outer diameter of tyre [mm].	784
Stat. radius (SLR) [mm]	357
Rolling circumference [mm].	2342
Tread depth (mm)	12,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 G	2180	90	Single	8,50	
134 J	2120	100	Single	8,50	
133 G	2060	90	Twin	8,50	
132 J	2000	100	Twin	8,50	