

TYRES

Product group	Tyres
Item number	10966070
Valid tyre size	8.25 R 15
LI / SI / PR	142 / 141 G (141 / 140 J)
TL/TT	TT
Brand	Semperit
Tread pattern	M222 Trailer-Steel



Bohnenkamp
■ ■ ● Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit M222 is a tyre for medium-sized truck trailers in local and long-distance transport.
- It is characterised by high loading capacities compared with standard trailer tyres.
- Its particularly wide tread enables even pressure distribution, slow wear and thus high mileage.
- The construction of the shoulder grooves provides very good driving stability.

Technical Informations

Item number	10966070
EAN	4024067002445
Valid tyre size	8.25 R 15
LI / SI / PR	142 / 141 G (141 / 140 J)
TL/TT	TT
Brand	Semperit
Tread pattern	M222 Trailer-Steel
Axle position truck	TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	27,85
Recommended rim size	6.50
Permitted rim size	5.50, 6.00, 7.00
Maximum air pressure [bar].	8,50
Section width (mm)	210
Outer diameter of tyre [mm].	848
Stat. radius (SLR) [mm]	383
Rolling circumference [mm].	2530
Tread depth (mm)	12,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 G	2650	90	Single	8,50	
141 J	2575	100	Single	8,50	
141 G	2575	90	Twin	8,50	
140 J	2500	100	Twin	8,50	