

TYRES

| | |
|-----------------|-------------|
| Product group | Tyres |
| Item number | 10966100 |
| Valid tyre size | 8.5 R 17.5 |
| LI / SI / PR | 121 / 120 L |
| TL/TT | TL |
| Brand | Semperit |
| Tread pattern | Runner F2 |



Bohnenkamp
■ ■ ● Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit Runner F2 is a truck tyre for steering axles for regional and long-distance transport.
- Its tread pattern design with flexible sipes guarantees excellent handling, even on wet roads.
- The optimum contact area and the special rubber compound ensure slow wear and high mileage.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10966100 |
| EAN | 4024067000823 |
| Valid tyre size | 8.5 R 17.5 |
| LI / SI / PR | 121 / 120 L |
| TL/TT | TL |
| Brand | Semperit |
| Tread pattern | Runner F2 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | FA |
| Rolling resistance | D |
| Wet grip | C |
| Rolling noise [db]. | 71 |
| Rolling noise level | A |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 24,79 |
| Recommended rim size | 6.00 |
| Permitted rim size | 5.25, 6.75 |
| Maximum air pressure [bar]. | 6,50 |
| Section width (mm) | 216 |
| Outer diameter of tyre [mm]. | 817 |
| Stat. radius (SLR) [mm] | 375 |
| Rolling circumference [mm]. | 2449 |
| Tread depth (mm) | 12,2 |

E-Ready

No

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 121 L | 1450 | 120 | Single | 6,50 | |
| 120 L | 1400 | 120 | Twin | 6,50 | |