

## TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 10966206        |
| Valid tyre size | 265 / 70 R 19.5 |
| LI / SI / PR    | 143 / 141 J     |
| TL/TT           | TL              |
| Brand           | Semperit        |
| Tread pattern   | Worker T2       |



Bohnenkamp  
Moving Professionals

**SEMPERIT**   
Seit 1906.

## Notes and features

- The Semperit Worker T2 is a truck tyre for drive axles for uneven surfaces like building sites, poorly maintained or snow-covered roads.
- The rough block tread pattern provides very good traction during the entire service life of the tyre and prevents the penetration of small stones.
- The especially cut-resistant tread compound and reinforced upper sidewall protect the tyre from damages.

## Technical Informations

|                              |                 |
|------------------------------|-----------------|
| Item number                  | 10966206        |
| EAN                          | 4024067749463   |
| Valid tyre size              | 265 / 70 R 19.5 |
| LI / SI / PR                 | 143 / 141 J     |
| TL/TT                        | TL              |
| Brand                        | Semperit        |
| Tread pattern                | Worker T2       |
| M+S                          | M+S             |
| 3PMSF                        | 3PMSF           |
| Axle position truck          | TR              |
| Rolling resistance           | D               |
| Wet grip                     | B               |
| Rolling noise [db].          | 73              |
| Rolling noise level          | A               |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 54,ECE 117  |
| Nettogewicht [kg] (gültig)   | 41,12           |
| Recommended rim size         | 7.50            |
| Permitted rim size           | 6.75, 8.25      |
| Maximum air pressure [bar].  | 8,50            |
| Section width (mm)           | 265             |
| Outer diameter of tyre [mm]. | 881             |
| Stat. radius (SLR) [mm]      | 401             |
| Rolling circumference [mm].  | 2644            |
| Tread depth (mm)             | 15,8            |

E-Ready

No

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 143 J | 2725               | 100          | Single        | 8,50                     |              |
| 141 J | 2575               | 100          | Twin          | 8,50                     |              |