

TYRES

Product group	Tyres
Item number	10966300
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 L
TL/TT	TL
Brand	Semperit
Tread pattern	M470 Trans-Steel



Bohnenkamp
■ ■ ● Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperi M470 Trans-Steel is a tyre for driving axles of trucks or light trucks in regional or long-haul transport.
- Its tread pattern with solid tread blocks guarantees very good traction, even on rain-soaked roads.
- Its extra wide tread ensures high mileage.

Technical Informations

Item number	10966300
EAN	4024067820025
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 L
TL/TT	TL
Brand	Semperit
Tread pattern	M470 Trans-Steel
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	76
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	56,11
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,50
Section width (mm)	279
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	489
Rolling circumference [mm].	3203
Tread depth (mm)	20,1

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 L	3150	120	Single	8,50	
145 L	2900	120	Twin	8,50	