

TYRES

| Product group | Tyres | |
|-----------------|---------------------------|--|
| Item number | 10966320 | |
| Valid tyre size | 275 / 70 R 22.5 | |
| LI / SI / PR | 150 / 145 J (152 / 148 F) | |
| TL/TT | TL | |
| Brand | Semperit | |
| Tread pattern | City A2 | |





Notes and features

- The Semperit City A2 is a bus tyre for public transport.
- It is highly suitable for city traffic with its special challenges of constant starting and braking.
- Its reinforced sidewall and cut-resistant rubber compound ensure a long service life in these conditions.
- The tyre is characterised by low noise emission and excellent handling in all weather conditions.



Technical Informations

| Item number | 10966320 |
|------------------------------|---------------------------|
| EAN | 4024067000625 |
| Valid tyre size | 275 / 70 R 22.5 |
| LI / SI / PR | 150 / 145 J (152 / 148 F) |
| TL/TT | TL |
| Brand | Semperit |
| Tread pattern | City A2 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | FA/RA |
| Rolling resistance | D |
| Wet grip | В |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 53,10 |
| Recommended rim size | 7.50 |
| Permitted rim size | 8.25 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 275 |
| Outer diameter of tyre [mm]. | 974 |
| Stat. radius (SLR) [mm] | 445 |
| Rolling circumference [mm]. | 2922 |
| Tread depth (mm) | 19,5 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| E-Ready | No |
|---------|----|
|---------|----|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 150 J | 3350 | 100 | Single | 9,00 | |
| 152 F | 3550 | 80 | Single | 9,00 | |
| 145 J | 2900 | 100 | Twin | 9,00 | |
| 148 F | 3150 | 80 | Twin | 9,00 | |