TYRES

Product group	Tyres
Item number	10966340
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2

SEMPERIT ⓢ

Seit 1906.

Notes and features

- The Semperit Runner F2 is a truck tyre for steering axles for regional and long-distance transport.

- Its tread pattern design with flexible sipes guarantees excellent handling, even on wet roads.

- The optimum contact area and the special rubber compound ensure slow wear and high mileage.

Bohnenkamp
Moving Professionals

Technical Informations

Item number	10966340
EAN	4024067000441
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	B
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	58,26
Recommended rim size	8.25
Permitted rim size	9.00
Maximum air pressure [bar].	8,50
Section width (mm)	295
Outer diameter of tyre [mm].	1062
Stat. radius (SLR) [mm]	487
Rolling circumference [mm].	3184
Tread depth (mm)	14,3

E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	8,50	
149 M	3250	130	Twin	8,50	