

TYRES

| Product group | Tyres | |
|-----------------|------------------|--|
| Item number | 10966390 | |
| Valid tyre size | 445 / 45 R 19.5 | |
| LI / SI / PR | 160 J, 22 PR | |
| TL/TT | TL | |
| Brand | Continental | |
| Tread pattern | Conti Hybrid HT3 | |





Notes and features

- The Continental Hybrid HT3 is a truck trailer tyre for mixed use in regional, local and long-distance traffic.
- The tyre offers a very long service life and low fuel consumption thanks to its optimised tread compound and a particularly flexible sidewall construction.
- Its tread with narrowed grooves ensures low wear and thus guarantees a long service life.



Technical Informations

| Item number | 10966390 |
|------------------------------|------------------|
| EAN | 4019238558784 |
| Valid tyre size | 445 / 45 R 19.5 |
| LI / SI / PR | 160 J, 22 PR |
| TL/TT | TL |
| Brand | Continental |
| Tread pattern | Conti Hybrid HT3 |
| M+S | M+S |
| Axle position truck | TR |
| Rolling resistance | В |
| Wet grip | С |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 69,00 |
| Recommended rim size | 14.0 |
| Permitted rim size | 15.0 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 436 |
| Outer diameter of tyre [mm]. | 895 |
| Stat. radius (SLR) [mm] | 421 |
| Rolling circumference [mm]. | 2792 |
| Tread depth (mm) | 13,0 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 160 J | 4500 | 100 | Single | 9,00 | |