

TYRES

Product group	Tyres	
Item number	10966392	
Valid tyre size	435 / 50 R 19.5	
LI / SI / PR	160 J	
TL/TT	TL	
Brand	Continental	
Tread pattern	Conti Hybrid HT3	





Notes and features

- The Continental Hybrid HT3 is a truck trailer tyre for mixed use in regional, local and long-distance traffic.
- The tyre offers a very long service life and low fuel consumption thanks to its optimised tread compound and a particularly flexible sidewall construction.
- Its tread with narrowed grooves ensures low wear and thus guarantees a long service life.



Technical Informations

Item number	10966392
EAN	4019238622461
Valid tyre size	435 / 50 R 19.5
LI / SI / PR	160 J
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3
M+S	M+S
Axle position truck	TR
Rolling resistance	В
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	69,10
Recommended rim size	14.00
Permitted rim size	15.00
Maximum air pressure [bar].	9,00
Section width (mm)	423
Outer diameter of tyre [mm].	921
Rolling circumference [mm].	2854
Tread depth (mm)	12,8
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100		9,00	