

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 10966410 | |
| Valid tyre size | 365 / 80 R 20 | |
| LI / SI / PR | 152 K | |
| TL/TT | TL | |
| Brand | Continental | |
| Tread pattern | MPT 81 | |





Notes and features

- The MPT 81 is most suitable for use on multi-purpose vehicles on paved and unpaved roads.
- Suitable for winter conditions.
- Large lug tread contact area.

- High-traction tread pattern.
- Increased traction and high mileage.
- Ensured mobility on soft soils.
- Quiet.



Technical Informations

| Item number | 10966410 |
|------------------------------|---------------|
| EAN | 4040658007835 |
| Valid tyre size | 365 / 80 R 20 |
| LI / SI / PR | 152 K |
| TL/TT | TL |
| Brand | Continental |
| Tread pattern | MPT 81 |
| M+S | M+S |
| Carcass properties | POR |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 72,70 |
| Recommended rim size | 11 |
| Permitted rim size | 12 |
| Maximum air pressure [bar]. | 6,00 |
| Section width (mm) | 378 |
| Outer diameter of tyre [mm]. | 1089 |
| Stat. radius (SLR) [mm] | 502 |
| Rolling circumference [mm]. | 3275 |
| Tread depth (mm) | 19,5 |
| E-Ready | No |
| | |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 152 K | 3550 | 110 | | 6,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.