

## **TYRES**

Product group	Tyres	
Item number	10966440	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	156 / 150 L (154 / 150 M)	
TL/TT	TL	
Brand	Semperit	
Tread pattern	Runner F2	





## Notes and features

- The Semperit Runner F2 is a truck tyre for steering axles for regional and long-distance transport.
- Its tread pattern design with flexible sipes guarantees excellent handling, even on wet roads.
- The optimum contact area and the special rubber compound ensure slow wear and high mileage.



## **Technical Informations**

Item number	10966440
EAN	4024067000465
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 L (154 / 150 M)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	С
Wet grip	В
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	63,56
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	315
Outer diameter of tyre [mm].	1096
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3282
Tread depth (mm)	15,3

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	120	Single	9,00	
154 M	3750	130	Single	9,00	
150 L	3350	120	Twin	9,00	
150 M	3350	130	Twin	9,00	