

TYRES

Product group	Tyres
Item number	10966460
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 K
TL/TT	TL
Brand	Semperit
Tread pattern	Worker F2



Bohnenkamp
Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit Worker F2 is a truck tyre for front axles for mixed on- and off-road use.
- It is characterised by excellent handling on difficult surfaces like sand or gravel.
- The sturdy tread compound protects the tyre from damages and ensures a long service life.

Technical Informations

Item number	10966460
EAN	4024067000700
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 K
TL/TT	TL
Brand	Semperit
Tread pattern	Worker F2
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	66,19
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	315
Outer diameter of tyre [mm].	1096
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3282
Tread depth (mm)	16,2

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	9,00	
150 K	3350	110	Twin	9,00	