

## TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 10966465        |
| Valid tyre size | 315 / 80 R 22.5 |
| LI / SI / PR    | 156 / 150 K     |
| TL/TT           | TL              |
| Brand           | Semperit        |
| Tread pattern   | Worker D2       |



Bohnenkamp  
■ ■ ● Moving Professionals

**SEMPERIT**   
Seit 1906.

## Notes and features

- The Semperit Worker D2 is a truck tyre for the drive axle for mixed on- and off-road use.
- It is characterised by excellent traction due to the optimum tread pattern design.
- The ideal tread pattern symmetry together with the abrasion-resistant rubber compound ensure even wear and a long service life.

## Technical Informations

|                              |                 |
|------------------------------|-----------------|
| Item number                  | 10966465        |
| EAN                          | 4024067750148   |
| Valid tyre size              | 315 / 80 R 22.5 |
| LI / SI / PR                 | 156 / 150 K     |
| TL/TT                        | TL              |
| Brand                        | Semperit        |
| Tread pattern                | Worker D2       |
| M+S                          | M+S             |
| 3PMSF                        | 3PMSF           |
| Axle position truck          | RA              |
| Rolling resistance           | D               |
| Wet grip                     | B               |
| Rolling noise [db].          | 75              |
| Rolling noise level          | B               |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 54,ECE 117  |
| Nettogewicht [kg] (gültig)   | 70,20           |
| Recommended rim size         | 9.00            |
| Permitted rim size           | 9.75            |
| Maximum air pressure [bar].  | 9,00            |
| Section width (mm)           | 315             |
| Outer diameter of tyre [mm]. | 1096            |
| Stat. radius (SLR) [mm]      | 500             |
| Rolling circumference [mm].  | 3282            |
| Tread depth (mm)             | 19,6            |

---

|         |    |
|---------|----|
| E-Ready | No |
|---------|----|

---

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 156 K | 4000               | 110          | Single        | 9,00                     |              |
| 150 K | 3350               | 110          | Twin          | 9,00                     |              |