

TYRES

Product group	Tyres
Item number	10966502
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3



Notes and features

- The Continental Hybrid HT3 is a truck trailer tyre for mixed use in regional, local and long-distance traffic.
- Its tread with narrowed grooves ensures low wear and thus guarantees a long service life.
- The tyre offers a very long service life and low fuel consumption thanks to its optimised tread compound and a particularly flexible sidewall construction.

Technical Informations

Item number	10966502
EAN	4019238038026
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3
M+S	M+S
Axle position truck	TR
Rolling resistance	B
Wet grip	B
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	72,60
Recommended rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	379
Outer diameter of tyre [mm].	1065
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3264
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	