Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	10966535
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2



SEMPERIT Seit 1906.

Notes and features

- The Semperit Runner F2 is a truck tyre for steering axles for regional and long-distance transport.
- Its tread pattern design with flexible sipes guarantees excellent handling, even on wet roads.
- The optimum contact area and the special rubber compound ensure slow wear and high mileage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10966535
EAN	4024067000427
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	В
Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	71,32
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	385
Outer diameter of tyre [mm].	1092
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3248
Tread depth (mm)	14,3

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

20.09.2024

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.