

TYRES

Product group	Tyres
Item number	10966550
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K
TL/TT	TL
Brand	Semperit
Tread pattern	M277



Bohnenkamp
Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit M277 is a trailer tyre for construction site vehicles in mixed or pure construction site use.
- The strong casing is particularly robust and protects against damages.
- The tyre has great self-cleaning properties.

Technical Informations

Item number	10966550
EAN	4024067002452
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K
TL/TT	TL
Brand	Semperit
Tread pattern	M277
M+S	M+S
Axle position truck	TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	75
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	68,73
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	385
Outer diameter of tyre [mm].	1092
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3248
Tread depth (mm)	16,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	