

## TYRES

|                 |                     |
|-----------------|---------------------|
| Product group   | Tyres               |
| Item number     | 11065105            |
| Valid tyre size | 215 / 70 R 15 C     |
| LI / SI / PR    | 109 / 107 S, 8 PR   |
| TL/TT           | TL                  |
| Brand           | Sailun              |
| Tread pattern   | Commercio 4 Seasons |



Bohnenkamp  
Moving Professionals

 **SAILUN**  
TYRE

## Notes and features

- The Commercio 4 Seasons by Sailun is an all-season tyre for light trucks.
- Its directional tread pattern with arrow-shaped blocks and deep grooves offers very good performance in all weather conditions.
- Due to its 3D grooves and sipes, water and snow are drained away efficiently.
- The tyre offers excellent grip and very good braking properties on dry as well as rain-soaked or snow-covered roads.
- The low-wear, rugged rubber compound and reinforced sidewall protect the tyre from damages and premature wear.

## Technical Informations

|                              |                     |
|------------------------------|---------------------|
| Item number                  | 11065105            |
| EAN                          | 6959655475494       |
| Valid tyre size              | 215 / 70 R 15 C     |
| LI / SI / PR                 | 109 / 107 S, 8 PR   |
| TL/TT                        | TL                  |
| Brand                        | Sailun              |
| Tread pattern                | Commercio 4 Seasons |
| M+S                          | M+S                 |
| 3PMSF                        | 3PMSF               |
| Rolling resistance           | C                   |
| Wet grip                     | A                   |
| Rolling noise [db].          | 72                  |
| Rolling noise level          | B                   |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 54,ECE 117      |
| Nettogewicht [kg] (gültig)   | 13,00               |
| Recommended rim size         | 6.50J               |
| Maximum air pressure [bar].  | 4,50                |
| Section width (mm)           | 215                 |
| Outer diameter of tyre [mm]. | 683                 |
| Stat. radius (SLR) [mm]      | 308                 |
| Rolling circumference [mm].  | 2083                |
| Tread depth (mm)             | 9,7                 |
| E-Ready                      | No                  |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 109 S | 1030               | 180          | Single        | 4,50                     |              |
| 107 S | 975                | 180          | Twin          | 4,50                     |              |