Bohnenkamp

05.02.2025

TYRES

Product group	Tyres	
Item number	11065115	
Valid tyre size	195 / 65 R 16 C	
LI / SI / PR	104 / 102 T, 8 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	Commercio 4 Seasons	





Notes and features

- The Commercio 4 Seasons by Sailun is an all-season tyre for light trucks.
- Its directional tread pattern with arrow-shaped blocks and deep grooves offers very good performance in all weather conditions.
- Due to its 3D grooves and sipes, water and snow are drained away efficiently.
- The tyre offers excellent grip and very good braking properties on dry as well as rain-soaked or snow-covered roads.
- The low-wear, rugged rubber compound and reinforced sidewall protect the tyre from damages and premature wear.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	11065115
EAN	6959655475517
Valid tyre size	195 / 65 R 16 C
LI / SI / PR	104 / 102 T, 8 PR
TL/TT	TL
Brand	Sailun
Tread pattern	Commercio 4 Seasons
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	12,09
Recommended rim size	6J
Maximum air pressure [bar].	4,75
Section width (mm)	195
Outer diameter of tyre [mm].	660
Stat. radius (SLR) [mm]	322
Rolling circumference [mm].	2013
Tread depth (mm)	9,7
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 T	900	190	Single	4,75	
102 T	850	190	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.