

TYRES

| Product group | Tyres | |
|-----------------|---------------------|--|
| Item number | 11065150 | |
| Valid tyre size | 235 / 65 R 16 C | |
| LI / SI / PR | 121 / 119 R, 10 PR | |
| TL/TT | TL | |
| Brand | Sailun | |
| Tread pattern | Commercio 4 Seasons | |





Notes and features

- The Commercio 4 Seasons by Sailun is an all-season tyre for light trucks.
- Its directional tread pattern with arrow-shaped blocks and deep grooves offers very good performance in all weather conditions.
- Due to its 3D grooves and sipes, water and snow are drained away efficiently.
- The tyre offers excellent grip and very good braking properties on dry as well as rain-soaked or snow-covered roads.
- The low-wear, rugged rubber compound and reinforced sidewall protect the tyre from damages and premature wear.



Technical Informations

| Item number | 11065150 |
|------------------------------|---------------------|
| EAN | 6959655466416 |
| Valid tyre size | 235 / 65 R 16 C |
| LI / SI / PR | 121 / 119 R, 10 PR |
| TL/TT | TL |
| Brand | Sailun |
| Tread pattern | Commercio 4 Seasons |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Rolling resistance | С |
| Wet grip | A |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 15,79 |
| Recommended rim size | 7J |
| Maximum air pressure [bar]. | 5,75 |
| Section width (mm) | 235 |
| Outer diameter of tyre [mm]. | 712 |
| Stat. radius (SLR) [mm] | 322 |
| Rolling circumference [mm]. | 2172 |
| Tread depth (mm) | 9,7 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 121 R | 1450 | 170 | Single | 5,75 | |
| 119 R | 1360 | 170 | Twin | 5,75 | |