Bohnenkamp Moving Professionals

14.03.2025

TYRES

| Product group | Tyres | |
|-----------------|--------------------|--|
| Item number | 11065245 | |
| Valid tyre size | 225 / 75 R 16 C | |
| LI / SI / PR | 121 / 120 R, 10 PR | |
| TL/TT | TL | |
| Brand | Sailun | |
| Tread pattern | Endure WSL1 | |





Notes and features

- The Endure WSL1 by Sailun is a winter tyre for light trucks.
- Its tread design with zigzag main grooves and serrated grooves in the tyre shoulder reliably drain away snow and water.
- The tyre is characterised by excellent braking performance and very good grip on wet and snowcovered roads

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 11065245 |
|------------------------------|--------------------|
| EAN | 6959655423242 |
| Valid tyre size | 225 / 75 R 16 C |
| LI / SI / PR | 121 / 120 R, 10 PR |
| TL/TT | TL |
| Brand | Sailun |
| Tread pattern | Endure WSL1 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Rolling resistance | C |
| Wet grip | В |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 15,58 |
| Recommended rim size | 6J |
| Maximum air pressure [bar]. | 5,75 |
| Section width (mm) | 223 |
| Outer diameter of tyre [mm]. | 744 |
| Dynamic radius [mm] | 361.92 |
| Tread depth (mm) | 10,0 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 121 R | 1450 | 170 | Single | 5,75 | |
| 120 R | 1400 | 170 | Twin | 5,75 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.